

SAFETY DATA SHEET

PLASTIC

Page: 1

Compilation date: 20.03.2017

Revision No: 1

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: PLASTIC

Product code: A1

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Filler for industrial or professional application. For information regarding additional possible application please email us or dial the indicated phone number as shown below. We will connect you with our responsible technical personnel.

1.3. Details of the supplier of the safety data sheet

Company name: AIRO CHEMIE

A. Schmiemann GmbH & Co KG

Carl-Leverkus Str. 27

D - 40764 Langenfeld

Deutschland

Tel: [+49] (0)2173 8538-0

Fax: [+49] (0)2173 8538-60

Email: labor@airo-chemie.com

1.4. Emergency telephone number

Emergency tel: [+49] (0)228 19240

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: STOT RE 1: H372; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Repr. 2: H361d; Skin Irrit. 2: H315

Most important adverse effects: Flammable liquid and vapour. Causes skin irritation. Causes serious eye irritation. Suspected of damaging the unborn child. Causes damage to organs [hearing organs] through prolonged or repeated exposure.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H361d: Suspected of damaging the unborn child.

H372: Causes damage to organs [hearing organs] through prolonged or repeated exposure.

SAFETY DATA SHEET

PLASTIC

Page: 2

Hazard pictograms: GHS02: Flame
GHS07: Exclamation mark
GHS08: Health hazard



Signal words: Danger

Precautionary statements: P102: Keep out of reach of children.
P241: Use explosion-proof electrical/ventilating/lighting equipment.
P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243: Take precautionary measures against static discharge.
P264: Wash hands thoroughly after handling.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+352: IF ON SKIN: Wash with plenty of water/.
P303+361+353: IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P332+313: If skin irritation occurs: Get medical advice/attention.
P337+313: If eye irritation persists: Get medical advice/attention.
P370+378: In case of fire: Use alcohol-resistant foam to extinguish.
P403+235: Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

STYRENE

EINECS	CAS	PBT / WEL	CLP Classification	Percent
202-851-5	100-42-5	-	Flam. Liq. 3: H226; Repr. 2: H361d; Acute Tox. 4: H332; STOT RE 1: H372; Skin Irrit. 2: H315; Eye Irrit. 2: H319	10-20%

Section 4: First aid measures

[cont...]

SAFETY DATA SHEET

PLASTIC

Page: 3

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method. Do not use equipment in clean-up procedure which may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

[cont...]

SAFETY DATA SHEET

PLASTIC

Page: 4

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from sources of ignition. Prevent the build up of electrostatic charge in the immediate area. Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Coated steel.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

STYRENE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	86 mg/m ³	2	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical equipment are not a source of ignition.

Respiratory protection: Respiratory protection not required.

Hand protection: Rubber gloves-thickness: 0,2 mm Rubber gloves. Breakthrough time of the glove material > 8 hours.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: White

Odour: Characteristic odour

Solubility in water: Slightly soluble

[cont...]

SAFETY DATA SHEET

PLASTIC

Page: 5

Also soluble in: Most organic solvents.

Viscosity: Highly viscous

Kinematic viscosity: n.V.

Viscosity test method: Kinematic viscosity in 10⁻⁶ m²/s at 40°C (ISO 3104/3105)

Boiling point/range°C: 145

Melting point/range°C: n.V.

Flammability limits %: lower: 1,1

upper: 8

Flash point°C: 34

Part.coeff. n-octanol/water: n.v.

Autoflammability°C: 480

Vapour pressure: 7 mbar

Relative density: 1,90 g/cm³

pH: n.a.

VOC g/l: 216

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.
Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

STYRENE

IVN	MUS	LD50	90	mg/kg
ORL	MUS	LD50	316	mg/kg

[cont...]

SAFETY DATA SHEET

PLASTIC

Page: 6

ORL	RAT	LD50	2650	mg/kg
-----	-----	------	------	-------

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Waste code number: 08 04 09

Disposal of packaging: Dispose of in a regulated landfill site or other method for hazardous or toxic wastes.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1263

14.2. UN proper shipping name

Shipping name: PAINT

[cont...]

SAFETY DATA SHEET

PLASTIC

Page: 7

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No

Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E

Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

Polyester resin for multi-component systems (base + hardener) must be declared with UN no. 3269 according to GGVS/ADR and IMDG-code.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H361d: Suspected of damaging the unborn child.

H372: Causes damage to organs <or state all organs affected, if known> through prolonged or repeated exposure <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.