

Carbon fiber hose \varnothing 9-42 mm

3,06 g/m


PROPERTIES

This **braided carbon fiber hose** is suitable for the production of pipes and profiles of most diverse kind.

The diameter of the hose can be changed by stretching or compressing.

The best mechanical characteristics in shear and torsion are reached with 45° fiber angle.

Processing is possible between 30° and 60°.



OVERVIEW

- extremely light and very stable
- \varnothing 36 mm with 45° fiber angle
- different diameters and braid angles possible
- applicable with epoxy and polyester resin systems
- vibration resistance
- low thermal expansion

Construction	
Material	Carbon
Fineness	6K
Binding	Braided hose

Properties	Unit	Set Point
Width: stretched / flat	mm	16 / 29
Wall thickness	mm	0,36

Please note that the actual values may deviate from these specifications by up to +/- 10 %.

PACKAGING

Carbon fiber hose \varnothing 9-42 mm 3,06 g/m	Roll length: 150 lfm	Article-No. 4ks6056100
---	--------------------------------	----------------------------------

INFORMATION

The information contained in this technical data sheet result from research and tests conducted in our Laboratories under precise conditions. It is the responsibility of the user to determine the suitability of Gößl & Pfaff GmbH products, under their own conditions before commencing with the proposed application. Gößl + Pfaff GmbH guarantee the conformity of their products with their specifications but cannot guarantee the compatibility of a product with any particular application. Gößl + Pfaff GmbH disclaim all responsibility for damage from any incident which results from the use of these products. The responsibility of Gößl + Pfaff GmbH is strictly limited to reimbursement or replacement of products which do not comply with the published specifications.