

Fillers and RenLease[™] Ancillaries for Epoxy and Polyurethane Systems

| Filler DT 077-1 | Colour: white Bulk density: 1.0 g/cm ³ Can be used with Epoxy and Polyurethane systems Packaging: 25 kg |
|------------------------------|---|
| Filler DT 078-1 | Colour: dark grey Bulk density: 1.0 g/cm ³ Can be used with Epoxy and Polyurethane systems Packaging: 25 kg |
| Filler DT 081 | Colour: grey Bulk density: 0,35 – 0,4 g/cm ³ Can be used with Epoxy and Polyurethane systems Packaging: 20 kg |
| Filler DT 082 | Colour: white Bulk density: 1,6 g/cm ³ Can be used with Epoxy and Polyurethane systems Packaging: 1000 kg or 15 kg or 6 x 1.5 kg |
| Glass Fibres QT 58 | Glass fibres For the production of coupling layers and backing structures with Epoxy and Polyurethane systems. Packaging: 20 kg or 25 kg |
| Thixotropic Agent DT 5039 | Colour: opaque Bulk density: 0,1- 0,15 g/cm ³ Cannot be used with Polyurethane systems. Packaging: 9 kg |
| RenLease™ QZ 5101 | Film forming Poly-Vinyl-Alcohol (P.V.A.) release agent which can also be used as a sealer for porous surfaces. Produces glossy mouldings. Packaging: 5 kg or 6 x 900gr. |
| RenLease™ QV 5110 | Cloth applied wax based release agent for general applications. Polishable to lustre. Packing: 20 kg or 12 x 1 kg |
| RenLease™ QZ 5111 | A liquid suspension of waxes in solvent for the release of general and intricate mould surfaces. Polishable to lustre. Packaging: 4 x 3.75 kg or 6 x 750 gr. |
| Storage | Fillers and ancillaries must be stored in a dry place in sealed containers at room temperature. |

Working condition

When handling the fillers and ancillaries described in this data sheet adequate dust extraction has to be in place and local health & safety guidelines must be observed.

| Handling precautions | Caution Vantico products are generally quite harmless to handle provided that certain precautions normally taken when handling chemicals are observed. The uncured materials must not, for instance, be allowed to come into contact with foodstuffs or food utensils, and measures should be taken to prevent the uncured materials from coming in contact with the skin, since people with particularly sensitive skin may be affected. The wearing of impervious rubber or plastic gloves will normally be necessary; likewise the use of eye protection. The skin should be thoroughly cleansed at the end of each working period by washing with soap and warm water. The use of solvents is to be avoided. Disposable paper - not cloth towels - should be used to dry the skin. Adequate ventilation of the working area is recommended. These precautions are described in greater detail in Vantico publication No. 24264/3/e Hygienic precautions for handling plastics products of Vantico and in the Vantico Material Safety Data sheets for the individual products. These publications are available on request and should be referred to for fuller information. |
|--|---|
| Vantico Limited Adhesives and Tooling | All recommendations for the use of our products, whether given by us in writing, verbally, or to be implied from the results of tests carried out by us, are based on the current state of our knowledge. Notwithstanding any such recommendations the Buyer shall remain responsible for satisfying himself that the products as supplied by us are suitable for his intended process or purpose. Since we cannot control the application, use or processing of the products, we cannot accept responsibility therefor. The Buyer shall ensure that the intended use of the products will not infringe any third party is intellectual property rights. We warrant that our products are free from defects in accordance with and subject to our general conditions of supply. |
| Duxford, Cambridge England CB2 4QA | |
| Tel: +44 (0) 1223 493 000 Fax: +44 (0) 1223 493 002 | © Vantico Ltd, 2002 |
| www.renshape.com | ® Ren and RenShape are registered trademarks of Vantico AG, Basel, Switzerland ™ RenPaste, RenGel, RenLam, RenCast, RenLease are trademarks of Vantico AG, Basel, Switzerland |